Air handling unit

# 11027131
# InspirAIR® Side 180 Classic

Dual-flow ventilation solution that beats to the rhythm of the occupants' lives.





## PRODUCT BENEFITS

The ideal range for installation in suspended ceilings or on the floor for new or renovated housing
For a «quick» installation and commissioning
Product performance and air quality benchmarks on the market

### Principles of operation

General and permanent ventilation of the dwelling with heat recovery from the extracted air to preheat the incoming air.
This air is purified by customizable filters that ensure healthy air in the home.

### Product description

Dual-flow ventilation solution with heat recovery that allows incoming air filtration and indoor air renewal without heat loss.

### Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment, Non-residential buildings

### Reference arguments

Aldes InspirAIR® Side, high efficiency double flow ventilation solution refreshes the air in your home by removing the ambient air and supplying filtered air through its efficient and customisable filters while recovering heat from the home when relevant.

Suitable for new construction or renovation projects, InspirAIR® Side can adapt to the needs of the occupants for their well-being and comfort.


We reserve the right to make changes without notice

Air handling unit

# 11027131
# InspirAIR® Side 180 Classic

## Main characteristics

material:
- PPE – recyclable expanded polypropylene

configuration:
- 4 spigots Ø 160 mm
- Condensate connection with Ø32 mm outlet

available flow rates:
- 150, 180 and 300 m³/h at 200 Pa.

The range that suits all installation projects in false ceilings or on the floor
- Best size/weight compromise on the market with weights from 12 to 14 kg maximum
- Different finishes to best meet user and home expectations: Prima, Classic, Classic DHU (with detection for automatic action against humidity peaks in the home), Classic ERV DHU (with enthalpic exchanger preserving the home's humidity level and with detection for automatic action against humidity peaks in the home)

For «quick» installation and commissioning:
- choice of airflow direction at commissioning
- unique electrical box design for easy connection of all desired accessories
- electrical cable included
- commissioning assistant included in the remote control for easy start-up

Product performance and air quality benchmarks on the market
- Multi-certified products with aerodynamic and thermal performances benchmarked on the market

Complete range of distribution boxes, networks, and associated grilles to guarantee a performant and durable network over time

Humidity sensor integrated into the product (DHU models)

The widest range of filters on the market

Numerous wireless sensors and controls available

## Supplementary characteristics

- Range with certified European Ecopassport
- Standard Modbus connection for Smart-home or BMS integration
- Exclusive radon mode
- Weekly programming possible via remote control or Aldes Connect app
- Compatible with the Aldes Connect app allowing residents to monitor and control their ventilation
- Range included in Aldes professional tools for study, selection, and costing

Air handling unit

# 11027131
# InspirAIR® Side 180 Classic

## Contents of kits

InspirAIR® Side;1
Mounting Kit;1
Particle Filter;1
Dust Filter;1

## Accessories

| Description | Variants |
|---|---|
| | 11027068 |
| | 11027069 |
| CMEV push button for BAHIA CURVE terminal | 11026011 |
| Duct-mounted heating coil– 0.3 kW | 11023487 |
| VEX40T internal preheating coil* | 11023225 |
| USB-RS-485 cable | 11023320 |
| | 11027074 |
| | 11027073 |
| | 11027071 |
| | 11091560 |

## Filters

| Variants |
|---|
| 11027055 |
| 11027060 |
| 11027061 |
| 11027056 |
| 11027062 |

## Associated services

Commissioning

## General data

| Variants | Available filters | Type of exchanger | Motor Type |
|---|---|---|---|
| 11027131 | dust: -Coarse 65%,> pollen: -Coarse 65%,> particles: -ePM10 50%,> fine particles: -ePM1 0 85%, -ePM2.5 65%.> bacteria: -ePM2.5 95%, -ePM1 80%.> VOCs: -ePM10 85%, -ePM2.5 65%. | Sensible | EC |

## Dimensional data

| Variants | H (mm) | L (mm) | P (mm) | Ø (mm) | Weight (kg) |
|---|---|---|---|---|---|
| 11027131 | 230 | 1040 | 595 | 160 | 12 |

## Airflow data

| Variants | Max. airflow (m³/h) |
|---|---|
| 11027131 | 180 |

## Electrical datas

| Variants | Voltage (V) | Frequency (Hz) | Max. power | Protection rating | Max. current (A) | Weighted electrical power (W–Th–C) |
|---|---|---|---|---|---|---|
| 11027131 | 230 | 50/60 | 135 | IP22 | 1,2 | 135 |

## Regulatory data

| Variants | Energy class – Average climate | Ventilation energy class – Average climate |
|---|---|---|
| 11027131 | A | A |


We reserve the right to make changes without notice